SEETRONIC

Product Data Sheet

产 品 规 格 书

Product Type 产品类型	IP65 WaterMerged power RJ45 sockets IP65 防水合并电源网络插座
Product Model 产品型号	SAC3FCE8-E-01
Customer Name 客户名称	

Manufacturer 生产方	Prepared 制作	Checked 审核	Approved 核准

Customer 客户方	Received 接受	Checked 审核	Confirmed 确认

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书

Product Type 产品类型	IP65 Water Merged power RJ45 sockets IP65 防水合并电源网络插座	
Product Model 产品型号	SAC3FCE8-E-01	

Product Features
产品特性

- Lockable three-core device power-out socket connector with contacts for linear, neutral and pre-adapted safety grounding
- Used for electrical connection under outdoor conditions with protection grade is IP65
- Match with SAC3MSC-01 and SE8MC-05-NEW/SE8MS-05 plug
- High current capacity rated at 16A/250V AC IEC and 20A/300V AC UL
- Complies with CAT5e according to TIA/EIA 568B and ISO/IEC 11801 standard
- Fast locking and unlocking for the front and rear feedthrough type, providing a guaranteed reliability for continuous and stable signal transmission under moving conditions

- 可锁定的三芯设备电源插座连接器，触点分别为火线、零线及接地线
- 用于室外环境的电气连接，防护等级 IP65
- 与 SAC3MSC-01 和 SE8MC-05-NEW /SE8MS-05 插头配套使用
- 高电流容量，16A / 250V AC IEC 和 20A / 300V AC UL
- 根据 TIA/EIA568B 和 ISO/IEC11801 标准，插座符合 CAT 5e，并兼容 5e 以下传输等级
- 为前后贯通式，快速制锁解锁，为移动条件下信号持续稳定传输提供可靠保障

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Power Electrical Parameters
电源电气参数

Item 项目	Specification 规格
Number of Contacts 触点数量	2 + PE
Rated Current 额定电流	16A IEC / 20A UL
Rated Voltage 额定电压	250V AC IEC / 300V AC UL
Contact Resistance 接触电阻	⩽ 5 mΩ
Dielectric Strength 绝缘强度	4000V DC / 2500V AC
Insulation Resistance 绝缘电阻	> 1000 MΩ

RJ45 Electrical Parameters
RJ45 电气参数

Item 项目	Specification 规格
Connection type 连接类型	RJ45
Gender 公母性	Female 母
Contact resistance 接触电阻	< 10 mΩ
Rated current 额定电流	0.5A/PIN
Rated voltage 额定电压	50 V
Insulation resistance 绝缘电阻	⩾ 0.5GΩ
Dielectric strength 绝缘强度	1 KV DC
Frequency range 带宽频率	1~100 MHz
Transmission performance 传输等级	CAT5e

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Power Mechanical Parameters
电源机械参数

Item 项目	Specification 规格
Service Life 使用寿命	> 1000 mating cycles > 1000 次使用周期
Cable Size 电线尺寸	2.5mm^2 /12 AWG

RJ45 Mechanical Parameters
RJ45 机械参数

Item 项目	Specification 规格
Insertion force 插入力	≤40 N
Chassis shape 底板规格	D-shape
Service life 使用寿命	> 1000 mating cycles > 1000 次使用周期

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Power&Rj45 Material and Environmental Parameters
Power&Rj45 材料和环境

Item 项目	Specification 规格
Housing 外壳	Zinc alloy 锌合金
Contacts 触点	Cu alloy 铜合金
Contact plating 触点电镀	Power： Ag Rj45:Au 电源：银 Rj45:金
Flame-retardant grade 阻燃等级	UL 94 V-0（Power）
Housing plating 外壳电镀	Cr 珍珠铬
Temperature range 使用温度范围	-25°C ~ +85°C
Protection degree 防护等级	IP65

Standards and Certifications
标准和认证

Standards 标准	UL60320-1 | GB/T 34989 | IEC61984 TIA/EIA 568B | IEC11801


Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书

Product Drawing
产品外形尺寸



Unit: mm

Packaging Method
包装方式

Blister box packaging
10 pcs per blister box, 30 pcs per inner carton, 4 inner carton per master carton (120 pcs per master carton)

吸塑盒包装
10 个/吸塑盒，30 个/内盒，4 个内盒/箱 (即 120 个/箱)

Accessory
配件

- ☑ No accessories 无配件
- ☐ Back fastener plate 安装固定件
- ☐ Screws and Nuts 螺丝和螺帽
- ☐ Other 其他

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023


sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书

Assembly Instructions
安装使用说明

Put the protective cover on the rear side of the socket and then install on the front of the panel. Finally, tighten the screws with 0.5 N • m torque in clockwise direction.


先将防水盖与插座互配，再将插座前装在箱体开孔处，最后将螺丝按顺时针方向用 0.5 N • m 扭矩拧紧。



Solder the conductor portion of the cable to the inner core pins (refer to the wiring diagram on the right).

将线缆导体部分与内芯插针/插孔焊接在一起 (参考右图接线方式)

Wiring 线序	IEC	UL
L	Brown 棕色	Black 黑色
N	Blue 蓝色	White 白色
Ground 地线	Green/Yellow 绿色/黄色	Green 绿色



Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com