SEETRONIC

Product Data Sheet
产 品 规 格 书

Product Type
产品类型
IP67 WaterMerged power sockets
IP67 防水电源插座

Product Model
产品型号
SAC3FDS-01

Customer Name
客户名称

Manufacturer **生产方**	**Prepared** **制作**	**Checked** **审核**	**Approved** **核准**

Customer **客户方**	**Received** **接受**	**Checked** **审核**	**Confirmed** **确认**

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书


Product Type 产品类型	**IP67 Water Merged power sockets** **IP67 防水电源插座**	
Product Model 产品型号	**SAC3FDS-01**	

Product Features
产品特性


- Lockable three-core device power-out socket connector with contacts for linear, neutral and pre-adapted safety grounding
- Used for electrical connection under outdoor conditions with protection grade is IP67
- Match with SAC3MSC-01B plug（As shown in the following figure）
- High current capacity rated at 16A/250V AC IEC and 20A/250V AC UL

- 可锁定的三芯设备电源插座连接器，触点分别为火线、零线及接地线
- 用于室外环境的电气连接，防护等级 IP65/IP67
- 与 SAC3MSC-01B 插头配套使用(如下图示)
- 高电流容量，16A / 250V AC IEC 和 20A / 250V AC UL

SAC3FDS-01B



互配
（mutual match）



SAC3MSC-01B

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Power Electrical Parameters
电源电气参数

Item 项目	Specification 规格
Number of Contacts 触点数量	2 + PE
Rated Current 额定电流	16A IEC/20A UL
Rated Voltage 额定电压	250V AC IEC /250V AC UL
Contact Resistance 接触电阻	≤ 5 mΩ
Dielectric Strength 绝缘强度	4000V DC/2500V AC
Insulation Resistance 绝缘电阻	> 1000 MΩ

Power Mechanical Parameters
电源机械参数

Item 项目	Specification 规格
Service Life 使用寿命	> 1000 mating cycles > 1000 次使用周期
Cable Size 电线尺寸	2.5mm^2/12 AWG

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Power Material and Environmental Parameters
Power 材料和环境

Item 项目	Specification 规格
Housing 外壳	PA 尼龙
Contacts 触点	Cu alloy 铜合金
Contact plating 触点电镀	Ag 银
Flame-retardant grade 阻燃等级	UL 94 V-0
Temperature range 使用温度范围	-25°C ~ +85°C
Protection degree 防护等级	IP65/IP67

Standards and Certifications
标准和认证

Standards 标准	UL60320-1 | GB/T 34989 | IEC61984
Certifications 认证	CQC：CQC25003494397 TUV：R 50637626 0001 ETL：5035514


Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书

Product Drawing
产品外形尺寸



Unit: mm

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com

SEETRONIC

Product Data Sheet
产 品 规 格 书

Packaging Method
包装方式

Socket packed by Single bag ,1 pc per PE bag ， 50pcs waterproof covers packed by one PE bag
50 pcs per inner carton, 5 inner cartons per master carton (250 pcs per master carton)

插座单袋包装，1 个/袋，防水盖 50 个/袋
50 个/内盒，5 个内盒/箱（即 250 个/箱）

Accessory
配件

☑ No accessories 无配件	☐ Back fastener plate 安装固定件
☐ Screws and Nuts 螺丝和螺帽	☐ Other 其他

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023


sales@seetronic-group.com
www.seetronic.com

Product Data Sheet
产 品 规 格 书

Assembly Instructions
安装使用说明

Put the protective cover on the rear side of the socket and then install on the front of the panel. Finally, tighten the screws with 0.5 N • m torque in clockwise direction.


先将防水盖与插座互配，再将插座前装在箱体开孔处，最后将螺丝按顺时针方向用 0.5 N • m 扭矩拧紧



Solder the conductor portion of the cable to the inner core pins (refer to the wiring diagram on the right).

将线缆导体部分与内芯插针/插孔焊接在一起 (参考右图接线方式)

Wiring 线序	IEC	UL
L	Brown 棕色	Black 黑色
N	Blue 蓝色	White 白色
Ground 地线	Green/Yellow 绿色/黄色	Green 绿色



Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.
以上规格和信息可能存在公差，并已更新。我们已尽一切努力确保本规格书发布时的正确性。

All Rights Reserved 2023
保留所有权利 2023

sales@seetronic-group.com
www.seetronic.com